



SOUND CURTAINS
BY SOUND SEAL

CEILING TILE COVERS

SPEC DATA SHEET

NBCT

LIGHT FIXTURE COVERS

Sound Seal's **Noise Barrier Ceiling Tile Covers** reduce sound transmission through standard suspended ceiling tile systems. The "B-10 LAG/1" Fiberglass" product combines a flexible 1-lb psf foil-faced loaded vinyl noise barrier with a 1" fiberglass decoupler to enhance its noise reduction properties.

FEATURES:

- Ceiling tiles are die cut to 3 sizes
- Easy installation; just lay on top of each light fixture
- Class A fire rated per ASTM E-84
- Nominal thickness: 1.0"
- Weight: 1.2 lb psf

APPLICATIONS:

- Installed over an existing suspended ceiling tile system to offer speech privacy between offices or to keep factory noise out of office areas. The fiberglass decoupler lifts the barrier up above the grid system so that there are no gaps between pieces.

NBCT LIGHT FIXTURE COVERS

SIZING

Standard sizes include:

- 24" x 24"
- 24" x 48"
- 30" x 30"
- 30" x 54"

ACOUSTICAL PERFORMANCE

Sound Absorption Coefficients at the Octave Band Frequencies							
Frequency (Hz)	125	250	500	1K	2K	4K	STC
NBCTC	11	16	24	30	35	35	27

ASTM E-90



SPECIFICATIONS:

Visit www.soundseal.com
or call **1.800.569.1294**

soundseal.com/nbctc



www.soundseal.com



A CATALYST ACOUSTICS GROUP COMPANY