



SOUND CURTAINS
BY SOUND SEAL

FLEXIBLE NOISE BARRIERS

SPEC DATA SHEET



B-10 CV

CLEAR VINYL NOISE BARRIER

B-10 CV is a transparent poly-vinyl chloride noise, wind and thermal barrier designed to minimize the passage of sound, heat, cold, or wind from one area to another while offering maximum visibility. B-10 CV is available in roll or strip form and is also available in a USDA approved version. This product meets the minimum requirements of flame resistance established by the California state fire marshal for products identified in Section 13115, California Health and Safety Code.

FEATURES:

- Offers significant noise reduction and visibility
- Nominal Thickness: 0.16"
- Temperature Range: 0° F to +150° F
- Weight 1.0 lb psf
- Thermal Conductivity 0.73 Btu/(hr)(sq.ft.)(deg. F/in)

APPLICATIONS:

- Used in manufacturing environments such as a sorting facility or food processing plant, as a window in an acoustical enclosure, or in other applications that require visibility



B-10 CV CLEAR VINYL NOISE BARRIER

ACOUSTICAL PERFORMANCE

Sound Absorption Coefficients at the Octave Band Frequencies							
Frequency (Hz)	125	250	500	1K	2K	4K	STC
B-10 CV	13	17	22	26	32	37	26

ASTM E-90

SIZING

Standard rolls measure 48" x 60' L, or in fabricated panels with grommets at the top and Velcro seals along each vertical edge. In strip form, rolls are available up to 300' long. Strips 8" cut to length are available with mounting holes punched 2" on center.



SPECIFICATIONS:

Visit www.soundseal.com
or call **1.800.569.1294**

soundseal.com/flexiblebarriers



www.soundseal.com



A CATALYST ACOUSTICS GROUP COMPANY