



**SOUND CURTAINS**  
BY SOUND SEAL

FLEXIBLE NOISE BARRIERS

SPEC DATA SHEET



## **B-5 CV**

### CLEAR VINYL NOISE BARRIER

**B-5 CV** is a transparent poly-vinyl chloride noise, wind and thermal barrier designed to minimize the passage of sound, heat, cold, or wind from one area to another while offering maximum visibility.

#### **FEATURES:**

- Offers significant noise reduction and visibility
- Nominal Thickness: 0.08"
- Weight 0.50 lb psf

#### **APPLICATIONS:**

- Used in manufacturing environments such as a sorting facility or food processing plant, as a window in an acoustical enclosure, or in other applications that require visibility



## B-5 CV CLEAR VINYL NOISE BARRIER

### ACOUSTICAL PERFORMANCE

| Sound Absorption Coefficients at the Octave Band Frequencies |     |     |     |    |    |    |     |
|--------------------------------------------------------------|-----|-----|-----|----|----|----|-----|
| Frequency (Hz)                                               | 125 | 250 | 500 | 1K | 2K | 4K | STC |
| B-5 CV                                                       | 8   | 13  | 17  | 22 | 27 | 31 | 20  |

ASTM E-90

### SIZING

Standard rolls measure 48" x 60' L, or in fabricated panels with grommets at the top and Velcro seals along each vertical edge. In strip form, rolls are available up to 300' long. Strips 8" cut to length are available with mounting holes punched 2" on center.



#### SPECIFICATIONS:

Visit [www.soundseal.com](http://www.soundseal.com)  
or call **1.800.569.1294**

[soundseal.com/flexiblebarriers](http://soundseal.com/flexiblebarriers)



[www.soundseal.com](http://www.soundseal.com) |     



A CATALYST ACOUSTICS GROUP COMPANY